

RCT型同軸式離心渦卷泵浦性能規格表

2極三相

型號	馬力數 (HP)	口徑		標準性能													
		吸入	吐出	10M	15M	20M	25M	30M	35M	40M	45M	50M	55M	60M	65M	70M	75M
		(inch)	(inch)														
RCT-0.5	1/2	1"	1"	65													
RCT-1	1	1.5"	1.5"	200	135												
RCT-1	1	1.5"	1.5"	195	155	100											
RCT-2	2	1.5"	1.5"	320	280	135											
RCT-2	2	2"	2"	335	265	95											
RCT-2	2	2"	2"	390	360	240	85										
RCT-3	3	2"	2"	485	390	280	165										
RCT-3	3	2"	2"	360	335	305	295	215	105								
RCT-3	3	2.5"	2.5"	655	500	320											
RCT-3	3	3"	3"	690	500	370											
RCT-5	5	2"	2"		490	485	400	375	250	100							
RCT-5	5	2.5"	2.5"	835	620	455	160										
RCT-5	5	3"	3"	855	670	455	160										
RCT-7.5	7.5	2"	2"			470	460	455	415	375	280	145					
RCT-7.5	7.5	3"	3"	1030	955	855	725	550	300								
RCT-7.5	7.5	4"	4"	1200	980	760											
RCT-10	10	2"	2"			450	440	435	425	420	395	375	320	260			
RCT-10	10	3"	3"	1100	900	875	760	670	535	375							

RCT型同軸式離心渦卷泵浦性能規格表

2極三相

型號	馬力數 (HP)	口徑		標準性能													
		吸入	吐出	10M	15M	20M	25M	30M	35M	40M	45M	50M	55M	60M	65M	70M	75M
		(inch)	(inch)														
RCT-10	10	4"	4"	1495	1310	1180	975	725									
RCT-15	15	3"	3"			1050	1020	995	925	855	760	670	565	335			
RCT-15	15	3"	3"						680	665	635	605	550	500	395	295	
RCT-15	15	4"	4"	1665	1610	1475	1250	970	600								
RCT-15	15	5"	5"	2835	2385	1910	1425	725									
RCT-20	20	3"	3"				1025	995	945	895	825	760	670	585			
RCT-20	20	4"	4"			755	745	735	720	715	690	670	635	600	540	480	365
RCT-20	20	4"	4"			1760	1650	1545	1310	955							
RCT-20	20	5"	5"		3000	2650	2270	1885	1275								
RCT-25	25	4"	4"			1185	1160	1140	1120	1100	1075	1050	1000	955	760	565	
RCT-25	25	5"	5"			2330	2250	2110	1750	1545	1150	620					
RCT-30	30	4"	4"					1770	1720	1680	1570	1460	1230	1000	700		
RCT-30	30	6"	6"		3880	3770	2780	2010									
RCT-40	40	4"	4"							1250	1220	1200	1190	1170	1160	1140	1050
RCT-40	40	5"	5"			2330		2270		2250	2220	2110	1830	1400			
RCT-40	40	6"	6"			4560	4080	3630	3040	2190							

※以上數值若有變動，恕不另行通知。