

RCT型同軸式離心渦卷泵浦性能規格表

4極三相

型號	馬力	口徑		標準性能								
		吸入	吐出	5M	10M	15M	20M	25M	30M	35M	40M	45M
	(HP)	(inch)	(inch)									
RCT-2	2	2"	2"	550	470	240						
RCT-3	3	2.5"	2.5"	830	720	480						
RCT-5	5	3"	3"	1000	850	670						
RCT-7.5	7.5	4"	4"	1490	1290	1030	720					
RCT-10	10	4"	4"	2170	1900	1560	1160					
RCT-10	10	5"	5"	2600	2000	1000						
RCT-15	15	4"	4"	2170	2100	2070	2040	1490				
RCT-15	15	5"	5"		2300	2140	1710	1140				
RCT-15	15	6"	6"	3500	2950	2220						
RCT-20	20	4"	4"			2300	1910	1400	500			
RCT-20	20	5"	5"		3340	3010	2490	1760				
RCT-20	20	6"	6"		3630	3310	2550	2030	1750			
RCT-25	25	5"	5"			3790	3190	2600	1490			
RCT-25	25	6"	6"		4760	4490	3560	2270				
RCT-25	25	8"	8"	6250	5190	3560						
RCT-30	30	6"	6"		4760	4520	4080	3130	1610			
RCT-30	30	6"	6"			4050	3590	3040	2300	1290		
RCT-30	30	8"	8"		5340	3690	1200					

RCT型同軸式離心渦卷泵浦性能規格表

4極三相

型號	馬力	口徑		標準性能								
		吸入	吐出	5M	10M	15M	20M	25M	30M	35M	40M	45M
	(inch)	(inch)										
RCT-40	40	6"	6"			3880	3790	3690	3280	2440		
RCT-40	40	8"	8"			6020	4760	2170				
RCT-50	50	8"	8"			7210	6410	5270	3630			
RCT-60	60	6"	6"			6440	6330	5710	5050	4300	3160	
RCT-60	60	8"	8"			8850	8360	6970	4940			
RCT-60	60	10"	10"		10200	8890	7040	5270				
RCT-75	75	8"	8"			9100	8400	6600	5600	3800		
RCT-75	75	10"	10"			9400	8600	7200	5100	2400		
RCT-100	100	10"	10"					11200	10200	8500	6500	3300
RCT-100	125	10"	10"					14500	13000	11000	10000	
RCT-150	150	12"	12"						15000	13600	12000	10000

※以上數值若有變動，恕不另行通知。