

## SB型聯軸式離心渦卷泵浦性能規格表

型號	馬力 (HP)	口徑		標準性能					
		吸入 (mm)	吐出 (mm)	揚程 (M)	水量 (LPM)	揚程 (M)	水量 (LPM)	揚程 (M)	水量 (LPM)
SB-50x32L62.2	3	50	32	25	270	27	200	27.5	150
SB-50x32L63.7	5	50	32	30	235	31	200	31.5	150
SB-50x32M63.7	5	50	32	30	350	35	275	37	235
SB-50x32M65.5	7.5	50	32	35	435	45	330	50	200
SB-50x32H67.5	10	50	32	50	387	57	300	60	235
SB-50x32H611	15	50	32	79	400	85	300	89	200
SB-50x32K618.5	25	50	32	86	470	95	350	100	150
SB-65x40L63.7	5	65	40	20	640	23	500	25	328
SB-65x40L65.5	7.5	65	40	27.5	750	30	650	34	350
SB-65x40M67.5	10	65	40	34	700	40	600	47.5	300
SB-65x40H611	15	65	40	50	650	58.5	500	65	275
SB-65x40H615	20	65	40	60	725	70	567	75	470
SB-65x40H618.5	25	65	40	70	750	80	600	84	470
SB-65x40K630	40	65	40	88	700	95	600	97.5	400
SB-65x50L67.5	10	65	50	23	1340	25	1220	29	700
SB-65x50L611	15	65	50	26.5	1420	30	1200	34	700
SB-65x50M611	15	65	50	29	1340	35	1060	38	700
SB-65x50M615	20	65	50	38	1500	45	1200	50	700
SB-65x50M618.5	25	65	50	45	1610	50	1360	68	725
SB-65x50H618.5	25	65	50	50	1360	60	1100	65	800
SB-65x50H622	30	65	50	60	1340	70	1000	76	700
SB-65x50H630	40	65	50	65	1500	74	1340	88	800
SB-65x50K637	50	65	50	88	1220	93.5	1000	99	600
SB-80x65L611	15	80	65	20	2214	25	1666	26.5	1420
SB-80x65L615	20	80	65	22	2357	25	2214	30	1638
SB-80x65M618.5	25	80	65	33	2357	35	2214	40	1666
SB-80x65M622	30	80	65	37	2500	40	2357	47.5	1500
SB-80x65H630	40	80	65	50	2357	54	2000	58.5	1500
SB-80x65H637	50	80	65	61.5	2357	65	2000	69	1500
SB-80x65H645	60	80	65	76	2500	83	2000	88	1200
SB-80x65K655	75	80	65	80	2500	93	2000	100	1000
SB-100x80M622	30	100	80	23	3500	30	3000	33.5	2500

## SB型聯軸式離心渦卷泵浦性能規格表

型號	馬力 (HP)	口徑		標準性能					
		吸入 (mm)	吐出 (mm)	揚程 (M)	水量 (LPM)	揚程 (M)	水量 (LPM)	揚程 (M)	水量 (LPM)
<b>SB-100x80M630</b>	40	100	80	35	3500	40	3000	45	2357
<b>SB-100x80M637</b>	50	100	80	30	4570	45	3500	50	3000
<b>SB-100x80H645</b>	60	100	80	48.5	4000	60	3000	63.5	2500
<b>SB-100x80H655</b>	75	100	80	60	4000	65	3500	70	3000
<b>SB-100x80K675</b>	100	100	80	70	4142	80	3500	90	2833
<b>SB-125x100H655</b>	75	125	100	30	6400	40	5500	45	5000
<b>SB-125x100H675</b>	100	125	100	50	6400	60	5583	69	4000
<b>SB-125x100H690</b>	125	125	100	60	6600	76	5000	80	4000
<b>SB-125x100K6110</b>	150	125	100	60	6600	85	5000	95	3500

※以上數值若有變動，恕不另行通知。